

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
11 December 2003 (11.12.2003)

PCT

(10) International Publication Number  
**WO 03/102680 A1**(51) International Patent Classification<sup>7</sup>: **G02F 1/13357**,  
F21V 29/00(21) International Application Number: **PCT/KR03/00286**

(22) International Filing Date: 10 February 2003 (10.02.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2002/0030718 31 May 2002 (31.05.2002) KR(71) Applicant (for all designated States except US): **SAM-SUNG ELECTRONICS CO., LTD.** [KR/KR]; 416, Maetan-dong, Paldal-gu, Suwon-si, 442-742 Gyeonggi-do (KR).


(72) Inventors; and

(75) Inventors/Applicants (for US only): **WON, Yong-Gwang** [KR/KR]; 102-1606 Giheungsamjeong seonbimaetul Apt., #289-12, Bora-ri, Giheung-eup, Yongin-si, 449-904 Gyeonggi-do (KR). **PARK, Jong-Dae** [KR/KR]; #474-301Changcheon-dong, Seodaemun-gu, 120-836 Seoul (KR). **LEE, Seok-Won** [KR/KR]; 523-1405, Jinsanmaeulsam-sung5cha APT., #1167, Pungdeokcheon-ri, Suji-eup, Yongin-si, 449-846 Gyeonggi-do (KR).(74) Agent: **PARK, Young-Woo**; 5F., Seil Building, #727-13, Yoksam-dong, Gangnam-gu, 135-921 Seoul (KR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,

[Continued on next page]

(54) Title: BACKLIGHT ASSEMBLY AND LIQUID CRYSTAL DISPLAY APPARATUS HAVING THE SAME

(57) **Abstract:** There are provided a backlight assembly (200) and an LCD apparatus (110) having the same. A lamp unit (210, 220) is received in a first receiving container (300) having a first bottom surface (350) and a first sidewall (310) so that the lamp unit (210) faces the first sidewall. The lamp unit (210, 220) and the first receiving container (300) are received in a second receiving container (500) having a second bottom surface (550) and a second sidewall (510). A heat transfer member (261, 263) comprised of metal material having superior heat conductivity makes contact with the second receiving container (500) through the lamp unit (210, 220). The heat emitted from the lamp unit (210, 263) and discharged to exterior. Accordingly, the backlight assembly and the LCD apparatus may improve display characteristics thereof.

WO 03/102680 A1